

Wall mounted unit

ATX-J3



Siesta



Econo mode



Night set mode



Comfort mode



Online controller
via app



Multi model
application

Siesta wall mounted unit providing high efficiency and comfort

- › Seasonal efficiency values up to A++
- › ECONO mode decreases power consumption so that other appliances that need large power consumption can be used
- › Comfort mode guarantees draught free operation by preventing that warm or cold air is directly blown on to the body
- › Titanium apatite photocatalytic air purification

- › filter removes airborne microscopic particles, powerfully decomposes odours and helps to prevent the propagation of bacteria, viruses, microbes to ensure a steady supply of clean air
- › Online controller (optional): control your indoor from any location with an app, via your local network or internet

ATX-J3 + ARX-K



Indoor unit		ATX	20J3	25J3	35J3
Casing	Colour		White		
Dimensions	Unit	HeightxWidthxDepth	mm		
			283x770x198		
Sound power level	Cooling/Heating		55/55		58/58
Sound pressure level	Cooling	High/Nom./Low/Silent operation	39/33/25/22	40/33/26/22	41/34/27/23
	Heating	High/Nom./Low/Silent operation	39/34/28/25	40/34/28/25	41/35/29/26
Control systems	Infrared remote control		ARC433A89		


Efficiency data		ATX + ARX	20J3 + 20K	25J3 + 25K	35J3 + 35K
Cooling capacity	Min./Nom./Max.	kW	1.3/2.0/2.6	1.3/2.5/3.0	1.3/3.3/3.8
Heating capacity	Min./Nom./Max.	kW	1.3/2.5/3.5	1.3/2.8/4.0	1.3/3.5/4.8
Power input	Cooling	Min./Nom./Max.	0.310/0.490/0.720	0.310/0.700/1.050	0.290/1.030/1.300
	Heating	Min./Nom./Max.	0.250/0.590/0.950	0.250/0.690/1.110	0.290/0.930/1.290
Seasonal efficiency (according to EN14825)	Cooling	Energy label		A++	
		Pdesign	kW	2.00	2.50
	SEER		6.11		6.15
	Annual energy consumption	kWh	115	142	188
Heating (Average climate)	Energy label			A+	
		Pdesign	kW	2.20	2.40
	SCOP		4.34	4.16	4.14
	Annual energy consumption	kWh	711	809	947
Nominal efficiency	EER		4.09	3.55	3.21
	COP		4.24	4.06	3.76
	Annual energy consumption	kWh	244	352	514
	Energy label	Cooling/Heating		A/A	

Outdoor unit		ARX	20K	25K	35K
Dimensions	Unit	HeightxWidthxDepth	mm		
			550x658x275		
Sound power level	Cooling		60		62
	Heating		61		62
Sound pressure level	Cooling	High	46		48
	Heating	High	47		48
Operation range	Cooling	Ambient	Min.-Max.	-10~-46	
	Heating	Ambient	Min.-Max.	-15~-18	
Refrigerant	Type/Charge/GWP		R-410A/2,087.5		
	Charge	kg/TCO ₂ eq	0.74/1.5		1.0/2.1
Power supply	Phase/Frequency/Voltage	Hz/V	1~/50/220-240		

EER/COP according to Eurovent 2012, for use outside EU only | Nominal efficiency: cooling at 35°/27° nominal load, heating at 7°/20° nominal load

Contains fluorinated greenhouse gases

Daikin Europe N.V. Naamloze Vennootschap · Zandvoordestraat 300 · 8400 Oostende · Belgium · www.daikin.eu · BE 0412 120 336 · RPR Oostende (Responsible Editor)



ECPEN15-036 03/15



Daikin Europe N.V. participates in the Eurovent Certification programme for Liquid Chilling Packages (LCP), Air handling units (AHU), Fan coil units (FCU) and variable refrigerant flow systems (VRF) Check ongoing validity of certificate online: www.eurovent-certification.com or using: www.certiflash.com



The present leaflet is drawn up by way of information only and does not constitute an offer binding upon Daikin Europe N.V. Daikin Europe N.V. has compiled the content of this leaflet to the best of its knowledge. No express or implied warranty is given for the completeness, accuracy, reliability or fitness for particular purpose of its content and the products and services presented therein. Specifications are subject to change without prior notice. Daikin Europe N.V. explicitly rejects any liability for any direct or indirect damage, in the broadest sense, arising from or related to the use and/or interpretation of this leaflet. All content is copyrighted by Daikin Europe N.V.