

Enhanced hot water comfort

- > Quiet operation: with 53 dBA, one of the most silent products in its kind
- > Easy handling: thanks to its compact size, it can easily pass through the doorway
- > Enhanced comfort: the 3 operating modes will
- give an answer to all your needs

 > Wide operation range: down to -7 °C outside
 temperature with the heat pump, below -7 °C
 electrical heating element support


EKHH2E-AV3



Single Unit				EKHH	2E200AV3	2E260AV3
COP					2.94 (1) / 3.30 (2)	3.10 (1) / 3.60 (2)
Heat pump	Casing	Colour			White body / grey top	
		Material			Cover: EPP top finishing	
	Operation range	Ambient	Min.	°CDB	-7	
			Max.	°CDB	3	8
	Power supply	Phase			1P	
		Frequency Hz		Hz	50	
		Voltage		V 230		
Tank	Casing	Colour			White	
		Material			Embossed ABS	
	Dimensions	Unit	Height	mm	1,210	1,500
	Operation range	e Water side Min. °C Max. °C		°C	10	
				°C	56	
	Standing heat loss			W	60	70
	Power supply	Phase			1P	
		Frequency Hz		Hz	50	
		Voltage V		V	230	

⁽¹⁾ Test at Ta DB/WB 7° C/ 6° C. According to EN 16147. (2) Test at Ta DB/WB 15° C/ 12° C. According to EN 16147.

Daikin Europe N.V. Naamloze Vennootschap · Zandvoordestraat 300 · 8400 Oostende · Belgium · www.daikin.eu · BE 0412 120 336 · RPR Oostende (Responsible Editor)



PEN18-780 04/18



The present leaflet is drawn up by way of information only and does not constitute an offer binding upon Daikin Europe N.V. Daikin Europe N.V. has compiled the content of this leaflet to the best of its knowledge. No express or implied warranty is given for the completeness, accuracy, reliability or fitness for particular purpose of its content and the products and services presented therein. Specifications are subject to change without prior notice. Daikin Europe N.V. explicitly rejects any liability for any direct or indirect damage, in the broadest sense, arising from or related to the use and/or interpretation of this leaflet. All content is copyrighted by Daikin Europe N.V.