

DAIKIN EDLA11D(3)V3 - EKHWSU(150-300)D3V3 ECODESIGN Data

Heating-Average Climate

EN 14511-2

	A7/W35	A7/W55
Heat output	10.56kW	10.64kW
El input	2.19kW	3.62kW
COP	4.83	2.94

EN 12102

	Low temperature	Medium temperature
Sound power level outdoor	62dB(A)	62dB(A)

EN 14825

	Low temperature	Medium temperature
η_s	182%	130%
Prated	10.00kW	10.00kW
SCOP	4.64	3.32
Tbiv	-10°C	-7°C
TOL	-10°C	-10°C
Pdh Tj = -7°C	9.20kW	9.30kW
COPd Tj = -7°C	3.03	1.90
Pdh Tj = +2°C	5.50kW	5.40kW
COPd Tj = +2°C	4.37	3.25
Pdh Tj = +7°C	4.60kW	4.40kW
COPd Tj = +7°C	6.74	4.81
Pdh Tj = +12°C	5.40kW	5.30kW
COPd Tj = +12°C	8.54	6.41
Pdh Tj = bivalent temperature	10.10kW	9.30kW
COPd Tj = bivalent temperature	2.58	1.90
Pdh Tj = TOL	10.10kW	7.60kW
COPd Tj = TOL	2.58	1.64
Cdh	1.00	1.00
WTOL	35°C	55°C

In accordance with 811, 812 and 813/2013 European Union Commission Regulations

POFF	23W	23W
PTO	23W	23W
PSB	23W	23W
PCK	0W	0W
Supplementary Heater: Type of energy input	Electrical	Electrical
Supplementary Heater: PSUP	0.00kW	2.40kW
Annual energy consumption QHE	4456kWh	6281kWh

Domestic Hot Water (DHW)-Average Climate – Separate DHW Tank

EN 16147	EKHWSU150D3V3	EKHWSU180D3V3	EKHWSU200D3V3	EKHWSU250D3V3	EKHWSU300D3V3
Declared load profile	L	L	L	L	L
Efficiency η_{dhw}	80%	105%	115%	107%	109%
Capacity of HP (kW)	11	11	11	11	11
Reference hot water temperature	51.8°C	51.8°C	52.5°C	47°C	52.5°C
Volume of DHW accounted in the test	145ltr	174ltr	192ltr	242ltr	292ltr
Tank DHW volume	150ltr	180ltr	200ltr	250ltr	300ltr
Stand-by heat losses	1.08kWh	1.2kWh	1.32kWh	1.44kWh	1.632kWh