

Product Information



Energy labelling Regulation: (EU) 811/2013

Ecodesign Regulation: (EU) 813/2013

PRODUCT FICHE

Heat pump combination heater		Indoor	EBLA08E23V3 / EKHWSU180D3V3
		Tank	EKHWSU180D3V3
Indoor unit sound power (*)		[dB(A)]	
Outdoor unit sound power (*)		[dB(A)]	62.0
Water heating	Declared load profile	-	L
	Energy efficiency class	-	A
Space Heating	Energy efficiency class 55°C (High temp. app.)	-	A++
Average climate (Design temperature = -10°C)			
Water heating	Water heating energy efficiency (η_{WH})	[%]	110
	Annual energy consumption	[kWh]	928
Space Heating	P_{rated} (declared heating capacity) @ -10°C	[kW]	8.0
	Seasonal space heating efficiency (η_{SH})	[%]	131
	Annual energy consumption	[kWh]	4,939
off peak operation function integrated in Heat pump		Y/N	false
Colder climate (Design temperature = -22°C)			
Water heating	Water heating energy efficiency (η_{WH})	[%]	90
	Annual electricity consumption (AEC)	[kWh]	1,142
Space Heating	P_{rated} (declared heating capacity) @ -22°C	[kW]	8.0
	Seasonal space heating efficiency (η_{SH})	[%]	112
	Annual energy consumption	[kWh]	6,864
Warmer climate (Design temperature = 2°C)			
Water heating	Water heating energy efficiency (η_{WH})	[%]	126
	Annual electricity consumption (AEC)	[kWh]	811
Space Heating	P_{rated} (declared heating capacity) @ 2°C	[kW]	8.1
	Seasonal space heating efficiency (η_{SH})	[%]	162
	Annual energy consumption	[kWh]	2,624
Ecodesign technical data			
Product description	Air-to-water heat pump	Y/N	Yes
	Water-to-water heat pump	Y/N	No
	Brine-to-water heat pump	Y/N	No
	Low-temperature heat pump	Y/N	No
	Equipped with a supplementary heater	Y/N	Yes
	Heat pump combination heater	Y/N	No
Air to water unit	Rated airflow (outdoor)	[m ³ /h]	3
Brine/water to water unit	Rated water/brine flow (outdoor H/E)	[m ³ /h]	3
Other	Capacity control	-	
	P_{off} (Power consumption Off mode)	[kW]	0.010
	P_{to} (Power consumption Thermostat off mode)	[kW]	0.010
	P_{sb} (Power consumption Standby mode)	[kW]	0.010
	P_{CK} (Power crankcase heater model)	[kW]	0.000
	Q_{elec} (Daily electricity consumption)	[kWh]	4.390
	Q_{fuel} (Daily fuel consumption)	[kWh]	
Part load conditions space heating average climate			
(A) condition (-7°C)		P_{dH} (declared heating capacity)	[kW] 6.9
		COP_d (declared COP)	- 1.96
		C_{dh} (degradation coefficient)	- 1.0
(B) condition (2°C)		P_{dH} (declared heating capacity)	[kW] 4.4
		COP_d (declared COP)	- 3.20
		C_{dh} (degradation coefficient)	- 1.0
(C) condition (7°C)		P_{dH} (declared heating capacity)	[kW] 3.3
		COP_d (declared COP)	- 4.64
		C_{dh} (degradation coefficient)	- 1.0
(D) (D) condition (12°C)		P_{dH} (declared heating capacity)	[kW] 4.1
		COP_d (declared COP)	- 6.22
		C_{dh} (degradation coefficient)	- 1.0
(E) ToI (temperature operating limit)		ToI (temperature operating limit)	[°C] -10
		P_{dH} (declared heating capacity)	[kW] 7.05
		COP_d (declared COP)	- 1.64
		WTOL (Heating water Operation Limit)	[°C] 55
(F) TbiValent temperature		T _{blv}	[°C] -8
		P_{dH} (declared heating capacity)	[kW] 7.5
		COP_d (declared COP)	- 1.90
Capacity of the back-up heater integrated in the unit		P_{sup} back-up heater (@T _{designh} : -10°C)	[kW]
Supplementary capacity at P _{design}		P_{sup} (@T _{designh} : -10°C)	[kW] 0.95
Details and precautions on installation, maintenance and assembly can be found in the installation and or operation manuals. Energy labels and product fiches for additional combinations, packages and other products can be found on 'energylabel.daikin.eu' (*) Sound power level in heating mode, measured according to the EN15036 for combustion boilers and EN 12102 for heat pumps under conditions of the EN ISO 3746, accuracy class 3 This data is for comparison of Energy efficiencies according to Regulation (EU) 2017/1369, for correct selection of products for your application, contact your dealer.			

Depending on your application and the product selected an additional supplementary heater may have to be installed.