

Product Information



Energy labelling Regulation: (EU) 811/2013

Ecodesign Regulation: (EU) 813/2013

PRODUCT FICHE

Heat pump combination heater		Indoor	EDLA09DA3V3 / EKHWSU250D3V3
		Tank	EKHWSU250D3V3
Indoor unit sound power (*)		[dB(A)]	
Outdoor unit sound power (*)		[dB(A)]	62.0
Water heating	Declared load profile	-	L
	Energy efficiency class	-	A
Space Heating	Energy efficiency class 55°C (High temp. app.)	-	A++
Average climate (Design temperature = -10°C)			
Water heating	Water heating energy efficiency (η_{WH})	[%]	107
	Annual energy consumption	[kWh]	961
Space Heating	P_{rated} (declared heating capacity) @ -10°C	[kW]	9.0
	Seasonal space heating efficiency (η_{SH})	[%]	133
	Annual energy consumption	[kWh]	
off peak operation function integrated in Heat pump		Y/N	false
Colder climate (Design temperature = -22°C)			
Water heating	Water heating energy efficiency (η_{WH})	[%]	89
	Annual electricity consumption (AEC)	[kWh]	1.156
Space Heating	P_{rated} (declared heating capacity) @ -22°C	[kW]	9.0
	Seasonal space heating efficiency (η_{SH})	[%]	117
	Annual energy consumption	[kWh]	
Warmer climate (Design temperature = 2°C)			
Water heating	Water heating energy efficiency (η_{WH})	[%]	126
	Annual electricity consumption (AEC)	[kWh]	813
Space Heating	P_{rated} (declared heating capacity) @ 2°C	[kW]	9.0
	Seasonal space heating efficiency (η_{SH})	[%]	162
	Annual energy consumption	[kWh]	
Ecodesign technical data			
Product description	Air-to-water heat pump	Y/N	Yes
	Water-to-water heat pump	Y/N	No
	Brine-to-water heat pump	Y/N	No
	Low-temperature heat pump	Y/N	No
	Equipped with a supplementary heater	Y/N	Yes
	Heat pump combination heater	Y/N	Yes
Air to water unit	Rated airflow (outdoor)	[m ³ /h]	2,880
Brine/water to water unit	Rated water/brine flow (outdoor H/E)	[m ³ /h]	
Other	Capacity control	-	Inverter
	P_{off} (Power consumption Off mode)	[kW]	0.023
	P_{to} (Power consumption Thermostat off mode)	[kW]	0.023
	P_{sb} (Power consumption Standby mode)	[kW]	0.023
	P_{CK} (Power crankcase heater model)	[kW]	0.000
	Q_{elec} (Daily electricity consumption)	[kWh]	4.560
	Q_{fuel} (Daily fuel consumption)	[kWh]	
Part load conditions space heating average climate			
(A) condition (-7°C)			
	P_{dh} (declared heating capacity)	[kW]	8.5
	COP_d (declared COP)	-	2.09
	C_{dh} (degradation coefficient)	-	1.0
(B) condition (2°C)			
	P_{dh} (declared heating capacity)	[kW]	5.0
	COP_d (declared COP)	-	3.28
	C_{dh} (degradation coefficient)	-	1.0
(C) condition (7°C)			
	P_{dh} (declared heating capacity)	[kW]	4.4
	COP_d (declared COP)	-	4.80
	C_{dh} (degradation coefficient)	-	1.0
(D) (D) condition (12°C)			
	P_{dh} (declared heating capacity)	[kW]	5.3
	COP_d (declared COP)	-	6.45
	C_{dh} (degradation coefficient)	-	1.0
(E) ToI (temperature operating limit)			
	ToI (temperature operating limit)	[°C]	-10
	P_{dh} (declared heating capacity)	[kW]	6.8
	COP_d (declared COP)	-	1.70
(F) TbiValent temperature			
	WTOL (Heating water Operation Limit)	[°C]	55
	T _{blv}	[°C]	-8
	P_{dh} (declared heating capacity)	[kW]	8.8
	COP_d (declared COP)	-	1.92
Capacity of the back-up heater integrated in the unit	P_{sup} back-up heater (@T _{designh} : -10°C)	[kW]	
Supplementary capacity at P _{design}	P_{sup} (@T _{designh} : -10°C)	[kW]	2.2
Details and precautions on installation, maintenance and assembly can be found in the installation and or operation manuals. Energy labels and product fiches for additional combinations, packages and other products can be found on 'energylabel.daikin.eu' (*) Sound power level in heating mode, measured according to the EN15036 for combustion boilers and EN 12102 for heat pumps under conditions of the EN ISO 3746, accuracy class 3 This data is for comparison of Energy efficiencies according to Regulation (EU) 2017/1369, for correct selection of products for your application, contact your dealer.			

Depending on your application and the product selected an additional supplementary heater may have to be installed.