

Model(s): EAVH16S23DA6V7 / EPGA11DAV37								
Air-to-water heat pump: Yes								
Water-to-water heat pump: No								
Brine-to-water heat pump: No								
Low-temperature heat pump: No								
Equipped with a supplementary heater: Yes								
Heat pump combination heater: Yes								
Parameters shall be declared for medium-temperature application, except for low-temperature heat pumps. For low-temperature heat pumps, parameters shall be declared for low-temperature application.								
Parameters shall be declared for average, colder and warmer climate conditions.								
Item	Symbol	Value	Unit		Item	Symbol	Value	Unit
Rated heat output ⁽³⁾	Prated	13	kW		Seasonal space heating energy efficiency	ηs	129	%
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature Tj					Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature Tj			
Tj = − 7 °C	Pdh	11.5	kW		Tj = − 7 °C	COPd or PERd	2.25 90.0	– or %
Tj = + 2 °C	Pdh	6.5	kW		Tj = + 2 °C	COPd or PERd	3.14 125.6	– or %
Tj = + 7 °C	Pdh	4.6	kW		Tj = + 7 °C	COPd or PERd	4.27 170.8	– or %
Tj = + 12 °C	Pdh	5.2	kW		Tj = + 12 °C	COPd or PERd	5.75 230.0	– or %
Tj = bivalent temperature	Pdh	12.5	kW		Tj = bivalent temperature	COPd or PERd	2.11 84.4	– or %
Tj = operation limit temperature	Pdh	12.5	kW		Tj = operation limit temperature	COPd or PERd	2.11 84.4	– or %
For air-to-air heat pumps: Tj = − 15 °C (if TOL < − 20 °C)	Pdh	12.1	kW		For air-to-air heat pumps: Tj = − 15 °C (if TOL < − 20 °C)	COPd or PERd	2.67 106.8	– or %
Bivalent temperature	Tbiv	-10	°C		For air-to-water heat pumps: Operation limit temperature	TOL	-10	°C
Cycling interval capacity for heating	Pcych		kW		Cycling interval efficiency	COPcyc or PERcyc		– or %
Degradation co-efficient ⁽⁴⁾	Cdh		—		Heating water operating limit temperature	WTOL	55	°C
Power consumption in modes other than active mode					Equipped with a supplementary heater:			
Off mode	P _{OFF}	0.021	kW		Rated heat output ⁽⁴⁾	P _{sup}	6.0	kW
Thermostat-off mode	P _{TO}	0.041	kW		Type of energy input			
Standby mode	P _{SB}	0.021	kW					
Crankcase heater mode	P _{CK}	0.000	kW					
Other items								
Capacity control	Variable							
Sound power level, indoor/outdoor	L _{WA}	44.0 / 64.0	dB					
Annual energy consumption	Q _{HE}	7,845 28.2	kWh or GJ					
For heat pump combination heater:								
Declared load profile	XL				Water heating energy efficiency	η _{wh}	111	%
Daily electricity consumption	Q _{elec}	7.110	kWh		Daily fuel consumption	Q _{fuel}		kWh
Annual electricity consumption	AEC	1,517	kWh		Annual fuel consumption	AFC		GJ
Daikin Europe N.V. - Zandvoordestraat 300, 8400 Oostende, Belgium		Daikin Europe N.V.						

⁽³⁾) For heat pump space heaters and heat pump combination heaters, the rated heat output 'Prated' is equal to the design load for heating 'Pdesignh', and the rated heat output of a supplementary heater 'Psup' is equal to the supplementary capacity for heating 'sup(Tj)'.

⁽⁴⁾) If 'Cdh' is not determined by measurement then the default degradation coefficient is 'Cdh'= 0,9.