

Product Information



Energy labelling Regulation: (EU) 811/2013

Ecodesign Regulation: (EU) 813/2013

PRODUCT FICHE

Heat pump combination heater		Outdoor	EPGA11DAV37
		Indoor	EAVZ16S23DA6V7
Indoor unit sound power (*)		[dB(A)]	44.0
Outdoor unit sound power (*)		[dB(A)]	64.0
Water heating	Declared load profile	-	XL
	Energy efficiency class	-	A
Space Heating	Energy efficiency class 55°C (High temp. app.)	-	A++
Average climate (Design temperature = -10°C)			
Water heating	Water heating energy efficiency (η_{WH})	[%]	111
	Annual energy consumption	[kWh]	1,517
Space Heating	P_{rated} (declared heating capacity) @ -10°C	[kW]	13
	Seasonal space heating efficiency (η_{SH})	[%]	129
	Annual energy consumption	[kWh]	7,845
off peak operation function integrated in Heat pump		Y/N	false
Colder climate (Design temperature = -22°C)			
Water heating	Water heating energy efficiency (η_{WH})	[%]	91
	Annual electricity consumption (AEC)	[kWh]	1,855
Space Heating	P_{rated} (declared heating capacity) @ -22°C	[kW]	13
	Seasonal space heating efficiency (η_{SH})	[%]	123
	Annual energy consumption	[kWh]	10,137
Warmer climate (Design temperature = 2°C)			
Water heating	Water heating energy efficiency (η_{WH})	[%]	129
	Annual electricity consumption (AEC)	[kWh]	1,304
Space Heating	P_{rated} (declared heating capacity) @ 2°C	[kW]	11
	Seasonal space heating efficiency (η_{SH})	[%]	156
	Annual energy consumption	[kWh]	3,696
Ecodesign technical data			
Product description	Air-to-water heat pump	Y/N	Yes
	Water-to-water heat pump	Y/N	No
	Brine-to-water heat pump	Y/N	No
	Low-temperature heat pump	Y/N	No
	Equipped with a supplementary heater	Y/N	Yes
	Heat pump combination heater	Y/N	Yes
Air to water unit	Rated airflow (outdoor)	[m ³ /h]	6,900
Brine/water to water unit	Rated water/brine flow (outdoor H/E)	[m ³ /h]	3
Other	Capacity control	-	Inverter
	P_{off} (Power consumption Off mode)	[kW]	0.021
	P_{to} (Power consumption Thermostat off mode)	[kW]	0.041
	P_{sb} (Power consumption Standby mode)	[kW]	0.021
	P_{CK} (Power crankcase heater model)	[kW]	0.000
	Q_{elec} (Daily electricity consumption)	[kWh]	7.110
	Q_{fuel} (Daily fuel consumption)	[kWh]	
Part load conditions space heating average climate			
(A) condition (-7°C)		P_{dh} (declared heating capacity)	[kW] 11.5
		COP_d (declared COP)	- 2.25
		C_{dh} (degradation coefficient)	- 1.0
(B) condition (2°C)		P_{dh} (declared heating capacity)	[kW] 6.5
		COP_d (declared COP)	- 3.14
		C_{dh} (degradation coefficient)	- 1.0
(C) condition (7°C)		P_{dh} (declared heating capacity)	[kW] 4.6
		COP_d (declared COP)	- 4.27
		C_{dh} (degradation coefficient)	- 0.96
(D) (D) condition (12°C)		P_{dh} (declared heating capacity)	[kW] 5.2
		COP_d (declared COP)	- 5.75
		C_{dh} (degradation coefficient)	- 0.95
(E) Tol (temperature operating limit)		Tol (temperature operating limit)	[°C] -10
		P_{dh} (declared heating capacity)	[kW] 12.5
		COP_d (declared COP)	- 2.11
		WTOL (Heating water Operation Limit)	[°C] 55
(F) Tbilv temperature		Tbilv	[°C] -10
		P_{dh} (declared heating capacity)	[kW] 12.5
		COP_d (declared COP)	- 2.11
Capacity of the back-up heater integrated in the unit		P_{sup} back-up heater (@Tdesignh: -10°C)	[kW] 6.0
Supplementary capacity at P_design		P_{sup} (@Tdesignh: -10°C)	[kW] 13

Details and precautions on installation, maintenance and assembly can be found in the installation and/or operation manuals.
 Energy labels and product fiches for additional combinations, packages and other products can be found on 'energylabel.daikin.eu'
 (*) Sound power level in heating mode, measured according to the EN15036 for combustion boilers and EN 12102 for heat pumps under conditions of the EN ISO 3746, accuracy class 3
 This data is for comparison of Energy efficiencies according to Regulation (EU) 2017/1369, for correct selection of products for your application, contact your dealer.
 Depending on your application and the product selected an additional supplementary heater may have to be installed.

