

Product Information



Energy labelling Regulation: (EU) 811/2013

Ecodesign Regulation: (EU) 813/2013

PRODUCT FICHE

Heat pump combination heater		Outdoor	EPGA11DAV37	
		Indoor	EABX16DF6V7	
		Tank	EKHWSU180D3V3	
Indoor unit sound power (*)		[dB(A)]	44.0	
Outdoor unit sound power (*)		[dB(A)]	64.0	
Water heating	Declared load profile	-	L	
	Energy efficiency class	-	A	
Space Heating	Energy efficiency class 55°C (High temp. app.)	-	A++	
Average climate (Design temperature = −10°C)				
Water heating	Water heating energy efficiency (η_{WH})	[%]	94	
	Annual energy consumption	[kWh]	1,139	
Space Heating	P_{rated} (declared heating capacity) @ −10°C	[kW]	13	
	Seasonal space heating efficiency (η (η_S))	[%]	130	
	Annual energy consumption	[kWh]	7,768	
	off peak operation function integrated in Heat pump	Y/N	false	
Colder climate (Design temperature = −22°C)				
Water heating	Water heating energy efficiency (η_{WH})	[%]	91	
	Annual electricity consumption (AEC)	[kWh]	1,175	
Space Heating	P_{rated} (declared heating capacity) @ −22°C	[kW]	13	
	Seasonal space heating efficiency (η (η_S))	[%]	124	
	Annual energy consumption	[kWh]	10,091	
	Warmer climate (Design temperature = 2°C)			
Water heating	Water heating energy efficiency (η_{WH})	[%]	128	
	Annual electricity consumption (AEC)	[kWh]	831	
Space Heating	P_{rated} (declared heating capacity) @ 2°C	[kW]	11	
	Seasonal space heating efficiency (η_S)	[%]	160	
	Annual energy consumption	[kWh]	3,603	
	Ecodesign technical data			
Product description	Air-to-water heat pump	Y/N	Yes	
	Water-to-water heat pump	Y/N	No	
	Brine-to-water heat pump	Y/N	No	
	Low-temperature heat pump	Y/N	No	
	Equipped with a supplementary heater	Y/N	No	
	Heat pump combination heater	Y/N	Yes	
Air to water unit	Rated airflow (outdoor)	[m ³ /h]	6,900	
Brine/water to water unit	Rated water/brine flow (outdoor H/E)	[m ³ /h]		
Other	Capacity control	-	Inverter	
	P_{off} (Power consumption Off mode)	[kW]	0.021	
	P_{to} (Power consumption Thermostat off mode)	[kW]	0.041	
	P_{sb} (Power consumption Standby mode)	[kW]	0.021	
	P_{CK} (Power crankcase heater model)	[kW]	0.000	
	Q_{elec} (Daily electricity consumption)	[kWh]	5.370	
	Q_{fuel} (Daily fuel consumption)	[kWh]		
Part load conditions space heating average climate				
(A) condition (-7°C)	P_{dh} (declared heating capacity)	[kW]	11.5	
	COP_d (declared COP)	-	2.25	
	Cdh (degradation coefficient)	-	1.0	
B) condition (2°C)	P_{dh} (declared heating capacity)	[kW]	6.5	
	COP_d (declared COP)	-	3.14	
	Cdh (degradation coefficient)	-	1.0	
(C) condition (7°C)	P_{dh} (declared heating capacity)	[kW]	4.6	
	COP_d (declared COP)	-	4.27	
	Cdh (degradation coefficient)	-	0.96	
(D) (D) condition (12°C)	P_{dh} (declared heating capacity)	[kW]	5.2	
	COP_d (declared COP)	-	5.75	
	Cdh (degradation coefficient)	-	0.95	
(E) Tol (temperature operating limit)	Tol (temperature operating limit)	[°C]	-10	
	P_{dh} (declared heating capacity)	[kW]	12.5	
	COP_d (declared COP)	-	2.11	
(F) Tbivalent temperature	WTOL (Heating water Operation Limit)	[°C]	55	
	T_{blv}	[°C]	-10	
	P_{dh} (declared heating capacity)	[kW]	12.5	
	COP_d (declared COP)	-	2.11	
Capacity of the back-up heater integrated in the unit		P_{sup} back-up heater (@Tdesignh: −10°C)	[kW]	6.0
Supplementary capacity at P_design		P_{sup} (@Tdesignh: −10°C)	[kW]	0.0
Details and precautions on installation, maintenance and assembly can be found in the installation and or operation manuals. Energy labels and product fiches for additional combinations, packages and other products can be found on 'energylabel.daikin.eu'				
(*) Sound power level in heating mode, measured according to the EN15036 for combustion boilers and EN 12102 for heat pumps under conditions of the EN ISO 3746, accuracy class 3				

This data is for comparison of Energy efficiencies according to Regulation (EU) 2017/1369, for correct selection of products for your application, contact your dealer.
Depending on your application and the product selected an additional supplementary heater may have to be installed.