

Model(s): EAVX16S18DA6V7 / EPGA16DAV37			
Air-to-water heat pump: Yes			
Water-to-water heat pump: No			
Brine-to-water heat pump: No			
Low-temperature heat pump: No			
Equipped with a supplementary heater: Yes			
Heat pump combination heater: Yes			
Parameters shall be declared for medium-temperature application, except for low-temperature heat pumps. For low-temperature heat pumps, parameters shall be declared for low-temperature application.			
Parameters shall be declared for average, colder and warmer climate conditions.			
Item	Symbol	Value	Unit
Rated heat output <sup>(3)</sup>	Prated	16	kW
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature Tj			
Tj = - 7 °C	Pdh	13.1	kW
Tj = + 2 °C	Pdh	8.7	kW
Tj = + 7 °C	Pdh	5.8	kW
Tj = + 12 °C	Pdh	5.2	kW
Tj = bivalent temperature	Pdh	12.9	kW
Tj = operation limit temperature	Pdh	13.2	kW
For air-to-air heat pumps: Tj = - 15 °C (if TOL < - 20 °C)	Pdh	14.6	kW
Bivalent temperature	Tbiv	-5	°C
Cycling interval capacity for heating	Pcych		kW
Degradation co-efficient <sup>(4)</sup>	Cdh		—
Power consumption in modes other than active mode			
Off mode	P <sub>OFF</sub>	0.021	kW
Thermostat-off mode	P <sub>TO</sub>	0.041	kW
Standby mode	P <sub>SB</sub>	0.021	kW
Crankcase heater mode	P <sub>CK</sub>	0.000	kW
Other items			
Capacity control	Variable		
Sound power level, indoor/outdoor	L <sub>WA</sub>	44.0 / 66.0	dB
Annual energy consumption	Q <sub>HE</sub>	9,628 34.7	kWh or GJ
For heat pump combination heater:			
Declared load profile	L		
Daily electricity consumption	Q <sub>elec</sub>	4.870	kWh
Annual electricity consumption	AEC	1,029	kWh
Daikin Europe N.V. - Zandvoordestraat 300, 8400 Oostende, Belgium		Daikin Europe N.V.	

Item	Symbol	Value	Unit
Seasonal space heating energy efficiency	η <sub>s</sub>	134	%
Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature Tj			
Tj = - 7 °C	COP <sub>d</sub> or PER <sub>d</sub>	2.23 89.2	— or %
Tj = + 2 °C	COP <sub>d</sub> or PER <sub>d</sub>	3.26 130.4	— or %
Tj = + 7 °C	COP <sub>d</sub> or PER <sub>d</sub>	4.62 184.8	— or %
Tj = + 12 °C	COP <sub>d</sub> or PER <sub>d</sub>	6.47 258.8	— or %
Tj = bivalent temperature	COP <sub>d</sub> or PER <sub>d</sub>	2.40 96.0	— or %
Tj = operation limit temperature	COP <sub>d</sub> or PER <sub>d</sub>	2.05 82.0	— or %
For air-to-air heat pumps: Tj = - 15 °C (if TOL < - 20 °C)	COP <sub>d</sub> or PER <sub>d</sub>	2.40 96.0	— or %
For air-to-water heat pumps: Operation limit temperature	TOL	-10	°C
Cycling interval efficiency	COP <sub>cyc</sub> or PER <sub>cyc</sub>		— or %
Heating water operating limit temperature	WTOL	55	°C
Equipped with a supplementary heater:			
Rated heat output <sup>(4)</sup>	P <sub>sup</sub>	6.0	kW
Type of energy input			
For air-to-water heat pumps: Rated air flow rate, outdoors	—	8,100	m³/h
For water- or brine-to-water heat pumps: Rated brine or water flow rate, outdoor heat exchanger	—		m³/h

Water heating energy efficiency	η <sub>wh</sub>	104	%
Daily fuel consumption	Q <sub>fuel</sub>		kWh
Annual fuel consumption	AFC		GJ

<sup>(3)</sup> ) For heat pump space heaters and heat pump combination heaters, the rated heat output 'Prated' is equal to the design load for heating 'Pdesignh', and the rated heat output of a supplementary heater 'Psup' is equal to the supplementary capacity for heating 'sup(Tj)'.

<sup>(4)</sup> ) If 'Cdh' is not determined by measurement then the default degradation coefficient is 'Cdh'= 0,9.