

**DAIKIN EPRA16DV3 16kW / ETBH16E(6V/9W) / EKHWSU(150-300)D3V3 ECODESIGN Data**  
**Heating-Average Climate**

EN 14511-2

	<b>A7/W35</b>	<b>A7/W55</b>
Heat output	9.0 kW	7.24 kW
El input	1.8 kW	2.41 kW
COP	5	3.01

EN 12102-1

	<b>Low temperature</b>	<b>Medium temperature</b>
Sound power level indoor	44 dB(A)	44 dB(A)
Sound power level outdoor	54 dB(A)	54 dB(A)

EN 14825

	<b>Low temperature</b>	<b>Medium temperature</b>
$\eta_s$	177%	140%
$P_{rated}$	12.5kW	13kW
SCOP	4.51	3.58
$T_{biv}$	-7°C	-10°C
TOL	-10°C	-10°C
$P_{dh} T_j = -7^\circ C$	11.1kW	11.2kW
$COP_d T_j = -7^\circ C$	3.12	2.47
$P_{dh} T_j = +2^\circ C$	6.7kW	6.9kW
$COP_d T_j = +2^\circ C$	4.44	3.56
$P_{dh} T_j = +7^\circ C$	5.7kW	6.9kW
$COP_d T_j = +7^\circ C$	5.84	4.44
$P_{dh} T_j = +12^\circ C$	6.0kW	6.2kW
$COP_d T_j = +12^\circ C$	7.4	5.72
$P_{dh} T_j = \text{bivalent temperature}$	11.1kW	12.2kW

COPd T <sub>j</sub> = bivalent temperature	3.12	2.19
P <sub>dh</sub> T <sub>j</sub> = TOL	11.1kW	12.2kW
COPd T <sub>j</sub> = TOL	2.76	2.19
C <sub>dh</sub>	1.00	1.00
WTOL	35°C	55°C
P <sub>OFF</sub>	21W	21W
P <sub>TO</sub>	41W	41W
P <sub>SB</sub>	21W	21W
P <sub>CK</sub>	0W	0W
Supplementary Heater: Type of energy input	Electrical	Electrical
Supplementary Heater: P <sub>SUP</sub>	1.40kW	0kW
Annual energy consumption Q <sub>HE</sub>	5726kWh	7211kWh

### Domestic Hot Water (DHW)-Average Climate – Separate DHW Tank

EN 16147	EKHWSU150D3V3	EKHWSU180D3V3	EKHWSU200D3V3	EKHWSU250D3V3	EKHWSU300D3V3
Declared load profile	L	L	L	XL	XL
Efficiency $\eta_{dhw}$	64%	96%	100%	100%	90%
Capacity of HP (kW)	14	14	14	14	14
Reference hot water temperature	51.8°C	51.8°C	51.8°C	47°C	47.9°C
Volume of DHW accounted in the test	145ltr	174ltr	192ltr	242ltr	292ltr
Tank DHW volume	150ltr	180ltr	200ltr	250ltr	300ltr
Stand-by heat losses	1.08kWh	1.2kWh	1.32kWh	1.44kWh	1.632kWh