

Model(s): ETBH12EF6V / EPRA08EAV3 / EKHWSU200D3V3																																																																																																																																																																											
Air-to-water heat pump: Yes																																																																																																																																																																											
Water-to-water heat pump: No																																																																																																																																																																											
Brine-to-water heat pump: No																																																																																																																																																																											
Low-temperature heat pump: No																																																																																																																																																																											
Equipped with a supplementary heater: No																																																																																																																																																																											
Heat pump combination heater: Yes																																																																																																																																																																											
Parameters shall be declared for medium-temperature application, except for low-temperature heat pumps. For low-temperature heat pumps, parameters shall be declared for low-temperature application.																																																																																																																																																																											
Parameters shall be declared for average, colder and warmer climate conditions.																																																																																																																																																																											
<table><tr><th>Item</th><th>Symbol</th><th>Value</th><th>Unit</th></tr><tr><td>Rated heat output ⁽³⁾</td><td><i>Prated</i></td><td>8.5</td><td>kW</td></tr><tr><td colspan="4">Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature <i>T_j</i></td></tr><tr><td><i>T_j</i> = − 7 °C</td><td><i>P_{dH}</i></td><td>7.6</td><td>kW</td></tr><tr><td><i>T_j</i> = + 2 °C</td><td><i>P_{dH}</i></td><td>4.6</td><td>kW</td></tr><tr><td><i>T_j</i> = + 7 °C</td><td><i>P_{dH}</i></td><td>3.0</td><td>kW</td></tr><tr><td><i>T_j</i> = + 12 °C</td><td><i>P_{dH}</i></td><td>3.7</td><td>kW</td></tr><tr><td><i>T_j</i> = bivalent temperature</td><td><i>P_{dH}</i></td><td>7.6</td><td>kW</td></tr><tr><td><i>T_j</i> = operation limit temperature</td><td><i>P_{dH}</i></td><td>7.0</td><td>kW</td></tr><tr><td>For air-to-air heat pumps: <i>T_j</i> = − 15 °C (if <i>TOL</i> < − 20 °C)</td><td><i>P_{dH}</i></td><td>6.0</td><td>kW</td></tr><tr><td>Bivalent temperature</td><td><i>T_{biv}</i></td><td>-7</td><td>°C</td></tr><tr><td>Cycling interval capacity for heating</td><td><i>P_{cycH}</i></td><td></td><td>kW</td></tr><tr><td>Degradation co-efficient ⁽⁴⁾</td><td><i>C_{dH}</i></td><td></td><td>—</td></tr><tr><td colspan="4">Power consumption in modes other than active mode</td></tr><tr><td>Off mode</td><td><i>P_{OFF}</i></td><td>0.021</td><td>kW</td></tr><tr><td>Thermostat-off mode</td><td><i>P_{TO}</i></td><td>0.024</td><td>kW</td></tr><tr><td>Standby mode</td><td><i>P_{SB}</i></td><td>0.021</td><td>kW</td></tr><tr><td>Crankcase heater mode</td><td><i>P_{CK}</i></td><td>0.000</td><td>kW</td></tr><tr><td colspan="4">Other items</td></tr><tr><td>Capacity control</td><td></td><td></td><td></td></tr><tr><td>Sound power level, indoor/outdoor</td><td><i>L_{WA}</i></td><td>44.0 / 53.0</td><td>dB</td></tr><tr><td>Annual energy consumption</td><td><i>Q_{HE}</i></td><td>5,142 19</td><td>kWh or GJ</td></tr></table>				Item	Symbol	Value	Unit	Rated heat output ⁽³⁾	<i>Prated</i>	8.5	kW	Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature <i>T_j</i>				<i>T_j</i> = − 7 °C	<i>P_{dH}</i>	7.6	kW	<i>T_j</i> = + 2 °C	<i>P_{dH}</i>	4.6	kW	<i>T_j</i> = + 7 °C	<i>P_{dH}</i>	3.0	kW	<i>T_j</i> = + 12 °C	<i>P_{dH}</i>	3.7	kW	<i>T_j</i> = bivalent temperature	<i>P_{dH}</i>	7.6	kW	<i>T_j</i> = operation limit temperature	<i>P_{dH}</i>	7.0	kW	For air-to-air heat pumps: <i>T_j</i> = − 15 °C (if <i>TOL</i> < − 20 °C)	<i>P_{dH}</i>	6.0	kW	Bivalent temperature	<i>T_{biv}</i>	-7	°C	Cycling interval capacity for heating	<i>P_{cycH}</i>		kW	Degradation co-efficient ⁽⁴⁾	<i>C_{dH}</i>		—	Power consumption in modes other than active mode				Off mode	<i>P_{OFF}</i>	0.021	kW	Thermostat-off mode	<i>P_{TO}</i>	0.024	kW	Standby mode	<i>P_{SB}</i>	0.021	kW	Crankcase heater mode	<i>P_{CK}</i>	0.000	kW	Other items				Capacity control				Sound power level, indoor/outdoor	<i>L_{WA}</i>	44.0 / 53.0	dB	Annual energy consumption	<i>Q_{HE}</i>	5,142 19	kWh or GJ	<table><tr><th>Item</th><th>Symbol</th><th>Value</th><th>Unit</th></tr><tr><td>Seasonal space heating energy efficiency</td><td><i>η_s</i></td><td>134</td><td>%</td></tr><tr><td colspan="4">Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature <i>T_j</i></td></tr><tr><td><i>T_j</i> = − 7 °C</td><td><i>COP_d or PER_d</i></td><td>2.21 88.5</td><td>— or %</td></tr><tr><td><i>T_j</i> = + 2 °C</td><td><i>COP_d or PER_d</i></td><td>3.37 134.8</td><td>— or %</td></tr><tr><td><i>T_j</i> = + 7 °C</td><td><i>COP_d or PER_d</i></td><td>4.48 179.2</td><td>— or %</td></tr><tr><td><i>T_j</i> = + 12 °C</td><td><i>COP_d or PER_d</i></td><td>5.98 239.4</td><td>— or %</td></tr><tr><td><i>T_j</i> = bivalent temperature</td><td><i>COP_d or PER_d</i></td><td>2.21 88.5</td><td>— or %</td></tr><tr><td><i>T_j</i> = operation limit temperature</td><td><i>COP_d or PER_d</i></td><td>1.93 77.2</td><td>— or %</td></tr><tr><td>For air-to-air heat pumps: <i>T_j</i> = − 15 °C (if <i>TOL</i> < − 20 °C)</td><td><i>COP_d or PER_d</i></td><td>2.60 103.8</td><td>— or %</td></tr><tr><td>For air-to-water heat pumps: Operation limit temperature</td><td><i>TOL</i></td><td>-10</td><td>°C</td></tr><tr><td>Cycling interval efficiency</td><td><i>COP_{cyc} or PER_{cyc}</i></td><td></td><td>— or %</td></tr><tr><td>Heating water operating limit temperature</td><td><i>WTOL</i></td><td>55</td><td>°C</td></tr><tr><td colspan="4">Equipped with a supplementary heater:</td></tr><tr><td>Rated heat output ⁽⁴⁾</td><td><i>P_{sup}</i></td><td>6.0</td><td>kW</td></tr><tr><td>Type of energy input</td><td></td><td></td><td></td></tr><tr><td colspan="4"></td></tr><tr><td>For air-to-water heat pumps: Rated air flow rate, outdoors</td><td>—</td><td></td><td>m³/h</td></tr><tr><td>For water- or brine-to-water heat pumps: Rated brine or water flow rate, outdoor heat exchanger</td><td>—</td><td></td><td>m³/h</td></tr></table>				Item	Symbol	Value	Unit	Seasonal space heating energy efficiency	<i>η_s</i>	134	%	Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature <i>T_j</i>				<i>T_j</i> = − 7 °C	<i>COP_d or PER_d</i>	2.21 88.5	— or %	<i>T_j</i> = + 2 °C	<i>COP_d or PER_d</i>	3.37 134.8	— or %	<i>T_j</i> = + 7 °C	<i>COP_d or PER_d</i>	4.48 179.2	— or %	<i>T_j</i> = + 12 °C	<i>COP_d or PER_d</i>	5.98 239.4	— or %	<i>T_j</i> = bivalent temperature	<i>COP_d or PER_d</i>	2.21 88.5	— or %	<i>T_j</i> = operation limit temperature	<i>COP_d or PER_d</i>	1.93 77.2	— or %	For air-to-air heat pumps: <i>T_j</i> = − 15 °C (if <i>TOL</i> < − 20 °C)	<i>COP_d or PER_d</i>	2.60 103.8	— or %	For air-to-water heat pumps: Operation limit temperature	<i>TOL</i>	-10	°C	Cycling interval efficiency	<i>COP_{cyc} or PER_{cyc}</i>		— or %	Heating water operating limit temperature	<i>WTOL</i>	55	°C	Equipped with a supplementary heater:				Rated heat output ⁽⁴⁾	<i>P_{sup}</i>	6.0	kW	Type of energy input								For air-to-water heat pumps: Rated air flow rate, outdoors	—		m³/h	For water- or brine-to-water heat pumps: Rated brine or water flow rate, outdoor heat exchanger	—		m³/h
Item	Symbol	Value	Unit																																																																																																																																																																								
Rated heat output ⁽³⁾	<i>Prated</i>	8.5	kW																																																																																																																																																																								
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature <i>T_j</i>																																																																																																																																																																											
<i>T_j</i> = − 7 °C	<i>P_{dH}</i>	7.6	kW																																																																																																																																																																								
<i>T_j</i> = + 2 °C	<i>P_{dH}</i>	4.6	kW																																																																																																																																																																								
<i>T_j</i> = + 7 °C	<i>P_{dH}</i>	3.0	kW																																																																																																																																																																								
<i>T_j</i> = + 12 °C	<i>P_{dH}</i>	3.7	kW																																																																																																																																																																								
<i>T_j</i> = bivalent temperature	<i>P_{dH}</i>	7.6	kW																																																																																																																																																																								
<i>T_j</i> = operation limit temperature	<i>P_{dH}</i>	7.0	kW																																																																																																																																																																								
For air-to-air heat pumps: <i>T_j</i> = − 15 °C (if <i>TOL</i> < − 20 °C)	<i>P_{dH}</i>	6.0	kW																																																																																																																																																																								
Bivalent temperature	<i>T_{biv}</i>	-7	°C																																																																																																																																																																								
Cycling interval capacity for heating	<i>P_{cycH}</i>		kW																																																																																																																																																																								
Degradation co-efficient ⁽⁴⁾	<i>C_{dH}</i>		—																																																																																																																																																																								
Power consumption in modes other than active mode																																																																																																																																																																											
Off mode	<i>P_{OFF}</i>	0.021	kW																																																																																																																																																																								
Thermostat-off mode	<i>P_{TO}</i>	0.024	kW																																																																																																																																																																								
Standby mode	<i>P_{SB}</i>	0.021	kW																																																																																																																																																																								
Crankcase heater mode	<i>P_{CK}</i>	0.000	kW																																																																																																																																																																								
Other items																																																																																																																																																																											
Capacity control																																																																																																																																																																											
Sound power level, indoor/outdoor	<i>L_{WA}</i>	44.0 / 53.0	dB																																																																																																																																																																								
Annual energy consumption	<i>Q_{HE}</i>	5,142 19	kWh or GJ																																																																																																																																																																								
Item	Symbol	Value	Unit																																																																																																																																																																								
Seasonal space heating energy efficiency	<i>η_s</i>	134	%																																																																																																																																																																								
Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature <i>T_j</i>																																																																																																																																																																											
<i>T_j</i> = − 7 °C	<i>COP_d or PER_d</i>	2.21 88.5	— or %																																																																																																																																																																								
<i>T_j</i> = + 2 °C	<i>COP_d or PER_d</i>	3.37 134.8	— or %																																																																																																																																																																								
<i>T_j</i> = + 7 °C	<i>COP_d or PER_d</i>	4.48 179.2	— or %																																																																																																																																																																								
<i>T_j</i> = + 12 °C	<i>COP_d or PER_d</i>	5.98 239.4	— or %																																																																																																																																																																								
<i>T_j</i> = bivalent temperature	<i>COP_d or PER_d</i>	2.21 88.5	— or %																																																																																																																																																																								
<i>T_j</i> = operation limit temperature	<i>COP_d or PER_d</i>	1.93 77.2	— or %																																																																																																																																																																								
For air-to-air heat pumps: <i>T_j</i> = − 15 °C (if <i>TOL</i> < − 20 °C)	<i>COP_d or PER_d</i>	2.60 103.8	— or %																																																																																																																																																																								
For air-to-water heat pumps: Operation limit temperature	<i>TOL</i>	-10	°C																																																																																																																																																																								
Cycling interval efficiency	<i>COP_{cyc} or PER_{cyc}</i>		— or %																																																																																																																																																																								
Heating water operating limit temperature	<i>WTOL</i>	55	°C																																																																																																																																																																								
Equipped with a supplementary heater:																																																																																																																																																																											
Rated heat output ⁽⁴⁾	<i>P_{sup}</i>	6.0	kW																																																																																																																																																																								
Type of energy input																																																																																																																																																																											
For air-to-water heat pumps: Rated air flow rate, outdoors	—		m³/h																																																																																																																																																																								
For water- or brine-to-water heat pumps: Rated brine or water flow rate, outdoor heat exchanger	—		m³/h																																																																																																																																																																								
For heat pump combination heater:																																																																																																																																																																											
<table><tr><td>Declared load profile</td><td>L</td><td></td><td></td></tr><tr><td>Daily electricity consumption</td><td><i>Q_{elec}</i></td><td>4.007</td><td>kWh</td></tr><tr><td>Annual electricity consumption</td><td><i>AEC</i></td><td>845</td><td>kWh</td></tr></table>				Declared load profile	L			Daily electricity consumption	<i>Q_{elec}</i>	4.007	kWh	Annual electricity consumption	<i>AEC</i>	845	kWh	<table><tr><td>Water heating energy efficiency</td><td><i>η_{wh}</i></td><td>121</td><td>%</td></tr><tr><td>Daily fuel consumption</td><td><i>Q_{fuel}</i></td><td></td><td>kWh</td></tr><tr><td>Annual fuel consumption</td><td><i>AFC</i></td><td></td><td>GJ</td></tr></table>				Water heating energy efficiency	<i>η_{wh}</i>	121	%	Daily fuel consumption	<i>Q_{fuel}</i>		kWh	Annual fuel consumption	<i>AFC</i>		GJ																																																																																																																																												
Declared load profile	L																																																																																																																																																																										
Daily electricity consumption	<i>Q_{elec}</i>	4.007	kWh																																																																																																																																																																								
Annual electricity consumption	<i>AEC</i>	845	kWh																																																																																																																																																																								
Water heating energy efficiency	<i>η_{wh}</i>	121	%																																																																																																																																																																								
Daily fuel consumption	<i>Q_{fuel}</i>		kWh																																																																																																																																																																								
Annual fuel consumption	<i>AFC</i>		GJ																																																																																																																																																																								
Daikin Europe N.V. - Zandvoordestraat 300, 8400 Oostende, Belgium		Daikin Europe N.V.																																																																																																																																																																									

⁽³⁾) For heat pump space heaters and heat pump combination heaters, the rated heat output 'Prated' is equal to the design load for heating 'Pdesignh', and the rated heat output of a supplementary heater 'Psup' is equal to the supplementary capacity for heating 'sup(Tj)'.

⁽⁴⁾) If 'Cdh' is not determined by measurement then the default degradation coefficient is 'Cdh'= 0,9.