

Model(s): EHBX08EA6V / ERGA06EAV3 / EKHWSU250D3V3																																																																																																																																																				
Air-to-water heat pump: Yes																																																																																																																																																				
Water-to-water heat pump: No																																																																																																																																																				
Brine-to-water heat pump: No																																																																																																																																																				
Low-temperature heat pump: No																																																																																																																																																				
Equipped with a supplementary heater: No																																																																																																																																																				
Heat pump combination heater: No																																																																																																																																																				
Parameters shall be declared for medium-temperature application, except for low-temperature heat pumps. For low-temperature heat pumps, parameters shall be declared for low-temperature application.																																																																																																																																																				
Parameters shall be declared for average, colder and warmer climate conditions.																																																																																																																																																				
<table><tr><th>Item</th><th>Symbol</th><th>Value</th><th>Unit</th></tr><tr><td>Rated heat output ⁽³⁾</td><td><i>Prated</i></td><td>7.0</td><td>kW</td></tr><tr><td colspan="4">Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature <i>T_j</i></td></tr><tr><td><i>T_j</i> = − 7 °C</td><td><i>Pdh</i></td><td>5.9</td><td>kW</td></tr><tr><td><i>T_j</i> = + 2 °C</td><td><i>Pdh</i></td><td>3.9</td><td>kW</td></tr><tr><td><i>T_j</i> = + 7 °C</td><td><i>Pdh</i></td><td>3.0</td><td>kW</td></tr><tr><td><i>T_j</i> = + 12 °C</td><td><i>Pdh</i></td><td>3.3</td><td>kW</td></tr><tr><td><i>T_j</i> = bivalent temperature</td><td><i>Pdh</i></td><td>6.1</td><td>kW</td></tr><tr><td><i>T_j</i> = operation limit temperature</td><td><i>Pdh</i></td><td>5.4</td><td>kW</td></tr><tr><td>For air-to-air heat pumps: <i>T_j</i> = − 15 °C (if <i>TOL</i> < − 20 °C)</td><td><i>Pdh</i></td><td></td><td>kW</td></tr><tr><td>Bivalent temperature</td><td><i>T_{biv}</i></td><td>-6</td><td>°C</td></tr><tr><td>Cycling interval capacity for heating</td><td><i>Pcyc</i></td><td></td><td>kW</td></tr><tr><td>Degradation co-efficient ⁽⁴⁾</td><td><i>Cdh</i></td><td></td><td>—</td></tr><tr><td colspan="4">Power consumption in modes other than active mode</td></tr><tr><td>Off mode</td><td><i>P_{OFF}</i></td><td>0.010</td><td>kW</td></tr><tr><td>Thermostat-off mode</td><td><i>P_{TO}</i></td><td>0.010</td><td>kW</td></tr><tr><td>Standby mode</td><td><i>P_{SB}</i></td><td>0.010</td><td>kW</td></tr><tr><td>Crankcase heater mode</td><td><i>P_{CK}</i></td><td>0.000</td><td>kW</td></tr><tr><td colspan="4">Other items</td></tr><tr><td>Capacity control</td><td colspan="3">Variable</td></tr><tr><td>Sound power level, indoor/outdoor</td><td><i>L_{WA}</i></td><td>42 / 60</td><td>dB</td></tr><tr><td>Annual energy consumption</td><td><i>Q_{HE}</i></td><td>4,405 15.9</td><td>kWh or GJ</td></tr></table>				Item	Symbol	Value	Unit	Rated heat output ⁽³⁾	<i>Prated</i>	7.0	kW	Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature <i>T_j</i>				<i>T_j</i> = − 7 °C	<i>Pdh</i>	5.9	kW	<i>T_j</i> = + 2 °C	<i>Pdh</i>	3.9	kW	<i>T_j</i> = + 7 °C	<i>Pdh</i>	3.0	kW	<i>T_j</i> = + 12 °C	<i>Pdh</i>	3.3	kW	<i>T_j</i> = bivalent temperature	<i>Pdh</i>	6.1	kW	<i>T_j</i> = operation limit temperature	<i>Pdh</i>	5.4	kW	For air-to-air heat pumps: <i>T_j</i> = − 15 °C (if <i>TOL</i> < − 20 °C)	<i>Pdh</i>		kW	Bivalent temperature	<i>T_{biv}</i>	-6	°C	Cycling interval capacity for heating	<i>Pcyc</i>		kW	Degradation co-efficient ⁽⁴⁾	<i>Cdh</i>		—	Power consumption in modes other than active mode				Off mode	<i>P_{OFF}</i>	0.010	kW	Thermostat-off mode	<i>P_{TO}</i>	0.010	kW	Standby mode	<i>P_{SB}</i>	0.010	kW	Crankcase heater mode	<i>P_{CK}</i>	0.000	kW	Other items				Capacity control	Variable			Sound power level, indoor/outdoor	<i>L_{WA}</i>	42 / 60	dB	Annual energy consumption	<i>Q_{HE}</i>	4,405 15.9	kWh or GJ		<table><tr><th>Item</th><th>Symbol</th><th>Value</th><th>Unit</th></tr><tr><td>Seasonal space heating energy efficiency</td><td><i>η_s</i></td><td>128</td><td>%</td></tr><tr><td colspan="4">Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature <i>T_j</i></td></tr><tr><td><i>T_j</i> = − 7 °C</td><td><i>COPd or PERd</i></td><td>1.98 79</td><td>— or %</td></tr><tr><td><i>T_j</i> = + 2 °C</td><td><i>COPd or PERd</i></td><td>3.16 126</td><td>— or %</td></tr><tr><td><i>T_j</i> = + 7 °C</td><td><i>COPd or PERd</i></td><td>4.49 180</td><td>— or %</td></tr><tr><td><i>T_j</i> = + 12 °C</td><td><i>COPd or PERd</i></td><td>6.10 244</td><td>— or %</td></tr><tr><td><i>T_j</i> = bivalent temperature</td><td><i>COPd or PERd</i></td><td>2.12 85</td><td>— or %</td></tr><tr><td><i>T_j</i> = operation limit temperature</td><td><i>COPd or PERd</i></td><td>1.53 61</td><td>— or %</td></tr><tr><td>For air-to-air heat pumps: <i>T_j</i> = − 15 °C (if <i>TOL</i> < − 20 °C)</td><td><i>COPd or PERd</i></td><td></td><td>— or %</td></tr><tr><td>For air-to-water heat pumps: Operation limit temperature</td><td><i>TOL</i></td><td>-10</td><td>°C</td></tr><tr><td>Cycling interval efficiency</td><td><i>COPcyc or PERcyc</i></td><td></td><td>— or %</td></tr><tr><td>Heating water operating limit temperature</td><td><i>WTOL</i></td><td>55</td><td>°C</td></tr></table>				Item	Symbol	Value	Unit	Seasonal space heating energy efficiency	<i>η_s</i>	128	%	Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature <i>T_j</i>				<i>T_j</i> = − 7 °C	<i>COPd or PERd</i>	1.98 79	— or %	<i>T_j</i> = + 2 °C	<i>COPd or PERd</i>	3.16 126	— or %	<i>T_j</i> = + 7 °C	<i>COPd or PERd</i>	4.49 180	— or %	<i>T_j</i> = + 12 °C	<i>COPd or PERd</i>	6.10 244	— or %	<i>T_j</i> = bivalent temperature	<i>COPd or PERd</i>	2.12 85	— or %	<i>T_j</i> = operation limit temperature	<i>COPd or PERd</i>	1.53 61	— or %	For air-to-air heat pumps: <i>T_j</i> = − 15 °C (if <i>TOL</i> < − 20 °C)	<i>COPd or PERd</i>		— or %	For air-to-water heat pumps: Operation limit temperature	<i>TOL</i>	-10	°C	Cycling interval efficiency	<i>COPcyc or PERcyc</i>		— or %	Heating water operating limit temperature	<i>WTOL</i>	55	°C
Item	Symbol	Value	Unit																																																																																																																																																	
Rated heat output ⁽³⁾	<i>Prated</i>	7.0	kW																																																																																																																																																	
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature <i>T_j</i>																																																																																																																																																				
<i>T_j</i> = − 7 °C	<i>Pdh</i>	5.9	kW																																																																																																																																																	
<i>T_j</i> = + 2 °C	<i>Pdh</i>	3.9	kW																																																																																																																																																	
<i>T_j</i> = + 7 °C	<i>Pdh</i>	3.0	kW																																																																																																																																																	
<i>T_j</i> = + 12 °C	<i>Pdh</i>	3.3	kW																																																																																																																																																	
<i>T_j</i> = bivalent temperature	<i>Pdh</i>	6.1	kW																																																																																																																																																	
<i>T_j</i> = operation limit temperature	<i>Pdh</i>	5.4	kW																																																																																																																																																	
For air-to-air heat pumps: <i>T_j</i> = − 15 °C (if <i>TOL</i> < − 20 °C)	<i>Pdh</i>		kW																																																																																																																																																	
Bivalent temperature	<i>T_{biv}</i>	-6	°C																																																																																																																																																	
Cycling interval capacity for heating	<i>Pcyc</i>		kW																																																																																																																																																	
Degradation co-efficient ⁽⁴⁾	<i>Cdh</i>		—																																																																																																																																																	
Power consumption in modes other than active mode																																																																																																																																																				
Off mode	<i>P_{OFF}</i>	0.010	kW																																																																																																																																																	
Thermostat-off mode	<i>P_{TO}</i>	0.010	kW																																																																																																																																																	
Standby mode	<i>P_{SB}</i>	0.010	kW																																																																																																																																																	
Crankcase heater mode	<i>P_{CK}</i>	0.000	kW																																																																																																																																																	
Other items																																																																																																																																																				
Capacity control	Variable																																																																																																																																																			
Sound power level, indoor/outdoor	<i>L_{WA}</i>	42 / 60	dB																																																																																																																																																	
Annual energy consumption	<i>Q_{HE}</i>	4,405 15.9	kWh or GJ																																																																																																																																																	
Item	Symbol	Value	Unit																																																																																																																																																	
Seasonal space heating energy efficiency	<i>η_s</i>	128	%																																																																																																																																																	
Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature <i>T_j</i>																																																																																																																																																				
<i>T_j</i> = − 7 °C	<i>COPd or PERd</i>	1.98 79	— or %																																																																																																																																																	
<i>T_j</i> = + 2 °C	<i>COPd or PERd</i>	3.16 126	— or %																																																																																																																																																	
<i>T_j</i> = + 7 °C	<i>COPd or PERd</i>	4.49 180	— or %																																																																																																																																																	
<i>T_j</i> = + 12 °C	<i>COPd or PERd</i>	6.10 244	— or %																																																																																																																																																	
<i>T_j</i> = bivalent temperature	<i>COPd or PERd</i>	2.12 85	— or %																																																																																																																																																	
<i>T_j</i> = operation limit temperature	<i>COPd or PERd</i>	1.53 61	— or %																																																																																																																																																	
For air-to-air heat pumps: <i>T_j</i> = − 15 °C (if <i>TOL</i> < − 20 °C)	<i>COPd or PERd</i>		— or %																																																																																																																																																	
For air-to-water heat pumps: Operation limit temperature	<i>TOL</i>	-10	°C																																																																																																																																																	
Cycling interval efficiency	<i>COPcyc or PERcyc</i>		— or %																																																																																																																																																	
Heating water operating limit temperature	<i>WTOL</i>	55	°C																																																																																																																																																	
Equipped with a supplementary heater:																																																																																																																																																				
Rated heat output ⁽⁴⁾		<i>P_{sup}</i>	6.0	kW																																																																																																																																																
Type of energy input																																																																																																																																																				
For air-to-water heat pumps: Rated air flow rate, outdoors		—	2,520.0	m³/h																																																																																																																																																
For water- or brine-to-water heat pumps: Rated brine or water flow rate, outdoor heat exchanger		—		m³/h																																																																																																																																																

For heat pump combination heater:							
Declared load profile		XL			Water heating energy efficiency		
Daily electricity consumption		<i>Q_{elec}</i>	6.04		kWh	Daily fuel consumption	
Annual electricity consumption		<i>AEC</i>	1,298		kWh	Annual fuel consumption	
Daikin Europe N.V. - Zandvoordestraat 300, 8400 Oostende, Belgium		Daikin Europe N.V.					

⁽³⁾) For heat pump space heaters and heat pump combination heaters, the rated heat output 'Prated' is equal to the design load for heating 'Pdesignh', and the rated heat output of a supplementary heater 'Psup' is equal to the supplementary capacity for heating 'sup(Tj)'.
⁽⁴⁾ If 'Cdh' is not determined by measurement then the default degradation coefficient is 'Cdh' = 0.9.