

Model(s): EHVZ08S23EA6V / ERGA06EAV3			
Air-to-water heat pump: Yes			
Water-to-water heat pump: No			
Brine-to-water heat pump: No			
Low-temperature heat pump: No			
Equipped with a supplementary heater: Yes			
Heat pump combination heater: Yes			
Parameters shall be declared for medium-temperature application, except for low-temperature heat pumps. For low-temperature heat pumps, parameters shall be declared for low-temperature application.			
Parameters shall be declared for average, colder and warmer climate conditions.			
Item	Symbol	Value	Unit
Rated heat output ⁽³⁾	Prated	7.0	kW
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature Tj			
Tj = - 7 °C	Pdh	5.9	kW
Tj = + 2 °C	Pdh	3.9	kW
Tj = + 7 °C	Pdh	3.0	kW
Tj = + 12 °C	Pdh	3.3	kW
Tj = bivalent temperature	Pdh	6.1	kW
Tj = operation limit temperature	Pdh	5.4	kW
For air-to-air heat pumps: Tj = - 15 °C (if TOL < - 20 °C)	Pdh		kW
Bivalent temperature	Tbiv	-6	°C
Cycling interval capacity for heating	Pcych		kW
Degradation co-efficient ⁽⁴⁾	Cdh		—
Power consumption in modes other than active mode			
Off mode	POFF	0.010	kW
Thermostat-off mode	PTO	0.010	kW
Standby mode	PSB	0.010	kW
Crankcase heater mode	PCK	0.000	kW
Other items			
Capacity control	Variable		
Sound power level, indoor/outdoor	LWA	42 / 60	dB
Annual energy consumption	QHE	4,441 16.0	kWh or GJ

Item	Symbol	Value	Unit
Seasonal space heating energy efficiency	ηs	127	%
Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature Tj			
Tj = - 7 °C	COPd or PERd	1.98 79	— or %
Tj = + 2 °C	COPd or PERd	3.16 126	— or %
Tj = + 7 °C	COPd or PERd	4.49 180	— or %
Tj = + 12 °C	COPd or PERd	6.10 244	— or %
Tj = bivalent temperature	COPd or PERd	2.12 85	— or %
Tj = operation limit temperature	COPd or PERd	1.53 61	— or %
For air-to-air heat pumps: Tj = - 15 °C (if TOL < - 20 °C)	COPd or PERd		— or %
For air-to-water heat pumps: Operation limit temperature	TOL	-10	°C
Cycling interval efficiency	COPcyc or PERcyc		— or %
Heating water operating limit temperature	WTOL	55	°C
Equipped with a supplementary heater:			
Rated heat output ⁽⁴⁾	Psup	6.0	kW
Type of energy input			
For air-to-water heat pumps: Rated air flow rate, outdoors			
	—	2,520.0	m³/h
For water- or brine-to-water heat pumps: Rated brine or water flow rate, outdoor heat exchanger			
	—		m³/h

For heat pump combination heater:			
Declared load profile	XL		
Daily electricity consumption	Qelec	5.900	kWh
Annual electricity consumption	AEC	1,267	kWh
Daikin Europe N.V. - Zandvoordestraat 300, 8400 Oostende, Belgium	Daikin Europe N.V.		

Water heating energy efficiency	ηwh	133	%
Daily fuel consumption	Qfuel		kWh
Annual fuel consumption	AFC		GJ

⁽³⁾) For heat pump space heaters and heat pump combination heaters, the rated heat output 'Prated' is equal to the design load for heating 'Pdesignh', and the rated heat output of a supplementary heater 'Psup' is equal to the supplementary capacity for heating 'sup(Tj)'.
⁽⁴⁾ If 'Cdh' is not determined by measurement then the default degradation coefficient is 'Cdh' = 0.9.