

Product Information



Energy labelling Regulation: (EU) 811/2013

Ecodesign Regulation: (EU) 813/2013

PRODUCT FICHE

Heat pump combination heater		Indoor	EGSAH06DA9W
Indoor unit sound power (*)	[dB(A)]	39.0	
Outdoor unit sound power (*)	[dB(A)]		
Water heating	Declared load profile	-	L
	Energy efficiency class	-	A+
Space Heating	Energy efficiency class 55°C (High temp. app.)	-	A++
Average climate (Design temperature = -10°C)			
Water heating	Water heating energy efficiency (η_{WH})	[%]	117
	Annual energy consumption	[kWh]	877
Space Heating	P_{rated} (declared heating capacity) @ -10°C	[kW]	6.2
	Seasonal space heating efficiency (η_{SH})	[%]	141
	Annual energy consumption	[kWh]	3,447
off peak operation function integrated in Heat pump		Y/N	false
Colder climate (Design temperature = -22°C)			
Water heating	Water heating energy efficiency (η_{WH})	[%]	117
	Annual electricity consumption (AEC)	[kWh]	877
Space Heating	P_{rated} (declared heating capacity) @ -22°C	[kW]	6.2
	Seasonal space heating efficiency (η_{SH})	[%]	152
	Annual energy consumption	[kWh]	3,820
Warmer climate (Design temperature = 2°C)			
Water heating	Water heating energy efficiency (η_{WH})	[%]	117
	Annual electricity consumption (AEC)	[kWh]	877
Space Heating	P_{rated} (declared heating capacity) @ 2°C	[kW]	6.2
	Seasonal space heating efficiency (η_{SH})	[%]	143
	Annual energy consumption	[kWh]	2,189
Ecodesign technical data			
Product description			
	Air-to-water heat pump	Y/N	No
	Water-to-water heat pump	Y/N	Yes
	Brine-to-water heat pump	Y/N	Yes
	Low-temperature heat pump	Y/N	No
	Equipped with a supplementary heater	Y/N	Yes
	Heat pump combination heater	Y/N	No
Air to water unit	Rated airflow (outdoor)	[m ³ /h]	3
Brine/water to water unit	Rated water/brine flow (outdoor H/E)	[m ³ /h]	1.3
Other			
	Capacity control	-	
	P_{off} (Power consumption Off mode)	[kW]	0.015
	P_{to} (Power consumption Thermostat off mode)	[kW]	0.024
	P_{sb} (Power consumption Standby mode)	[kW]	0.015
	P_{CK} (Power crankcase heater model)	[kW]	0.000
	Q_{elec} (Daily electricity consumption)	[kWh]	4.140
	Q_{fuel} (Daily fuel consumption)	[kWh]	0.000
Part load conditions space heating average climate			
(A) condition (-7°C)			
	P_{dh} (declared heating capacity)	[kW]	5.5
	COP_d (declared COP)	-	3.13
	C_{dh} (degradation coefficient)	-	1.0
(B) condition (2°C)			
	P_{dh} (declared heating capacity)	[kW]	3.3
	COP_d (declared COP)	-	3.81
	C_{dh} (degradation coefficient)	-	1.0
(C) condition (7°C)			
	P_{dh} (declared heating capacity)	[kW]	2.2
	COP_d (declared COP)	-	4.33
	C_{dh} (degradation coefficient)	-	1.0
(D) (D) condition (12°C)			
	P_{dh} (declared heating capacity)	[kW]	1.0
	COP_d (declared COP)	-	3.65
	C_{dh} (degradation coefficient)	-	1.0
(E) Tol (temperature operating limit)			
	Tol (temperature operating limit)	[°C]	-10
	P_{dh} (declared heating capacity)	[kW]	6.4
	COP_d (declared COP)	-	2.90
	WTOL (Heating water Operation Limit)	[°C]	
(F) TbiValent temperature			
	T_{blv}	[°C]	-10
	P_{dh} (declared heating capacity)	[kW]	6.4
	COP_d (declared COP)	-	2.90
Capacity of the back-up heater integrated in the unit	P_{sup} back-up heater (@Tdesignh: -10°C)	[kW]	
Supplementary capacity at P_design	P_{sup} (@Tdesignh: -10°C)	[kW]	

Details and precautions on installation, maintenance and assembly can be found in the installation and or operation manuals.

Energy labels and product fiches for additional combinations, packages and other products can be found on 'energylabel.daikin.eu'

(*) Sound power level in heating mode, measured according to the EN15036 for combustion boilers and EN 12102 for heat pumps under conditions of the EN ISO 3746, accuracy class 3

This data is for comparison of Energy efficiencies according to Regulation (EU) 2017/1369, for correct selection of products for your application, contact your dealer.

Depending on your application and the product selected an additional supplementary heater may have to be installed.

