

Model(s): EGSAH06DA9W								
Air-to-water heat pump: No								
Water-to-water heat pump: Yes								
Brine-to-water heat pump: Yes								
Low-temperature heat pump: No								
Equipped with a supplementary heater: Yes								
Heat pump combination heater: No								
Parameters shall be declared for medium-temperature application, except for low-temperature heat pumps. For low-temperature heat pumps, parameters shall be declared for low-temperature application.								
Parameters shall be declared for average, colder and warmer climate conditions.								
Item	Symbol	Value	Unit		Item	Symbol	Value	Unit
Rated heat output <sup>(3)</sup>	<i>Prated</i>	6.2	kW		Seasonal space heating energy efficiency	$\eta_s$	141	%
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature $T_j$					Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature $T_j$			
$T_j = - 7\text{ °C}$	<i>Pdh</i>	5.5	kW		$T_j = - 7\text{ °C}$	<i>COPd or PERd</i>	3.13	– or %
$T_j = + 2\text{ °C}$	<i>Pdh</i>	3.3	kW		$T_j = + 2\text{ °C}$	<i>COPd or PERd</i>	3.81	– or %
$T_j = + 7\text{ °C}$	<i>Pdh</i>	2.2	kW		$T_j = + 7\text{ °C}$	<i>COPd or PERd</i>	4.33	– or %
$T_j = + 12\text{ °C}$	<i>Pdh</i>	1.0	kW		$T_j = + 12\text{ °C}$	<i>COPd or PERd</i>	3.65	– or %
$T_j$ = bivalent temperature	<i>Pdh</i>	6.4	kW		$T_j$ = bivalent temperature	<i>COPd or PERd</i>	2.90	– or %
$T_j$ = operation limit temperature	<i>Pdh</i>	6.4	kW		$T_j$ = operation limit temperature	<i>COPd or PERd</i>	2.90	– or %
For air-to-air heat pumps: $T_j = - 15\text{ °C}$ (if $TOL < - 20\text{ °C}$ )	<i>Pdh</i>		kW		For air-to-air heat pumps: $T_j = - 15\text{ °C}$ (if $TOL < - 20\text{ °C}$ )	<i>COPd or PERd</i>		– or %
Bivalent temperature	$T_{biv}$	-10	°C		For air-to-water heat pumps: Operation limit temperature	<i>TOL</i>	-10	°C
Cycling interval capacity for heating	<i>Pcych</i>		kW		Cycling interval efficiency	<i>COPcyc or PERcyc</i>		– or %
Degradation co-efficient <sup>(4)</sup>	<i>Cdh</i>		—		Heating water operating limit temperature	<i>WTOL</i>		°C
Power consumption in modes other than active mode					Equipped with a supplementary heater:			
Off mode	<i>P<sub>OFF</sub></i>	0.015	kW		Rated heat output <sup>(4)</sup>	<i>P<sub>sup</sub></i>		kW
Thermostat-off mode	<i>P<sub>TO</sub></i>	0.024	kW					
Standby mode	<i>P<sub>SB</sub></i>	0.015	kW		Type of energy input			
Crankcase heater mode	<i>P<sub>CK</sub></i>	0.000	kW					
Other items								
Capacity control					For air-to-water heat pumps: Rated air flow rate, outdoors	—		m³/h
Sound power level, indoor/outdoor	<i>L<sub>WA</sub></i>	39.0 /	dB		For water- or brine-to-water heat pumps: Rated brine or water flow rate, outdoor heat exchanger	—	1.3	m³/h
Annual energy consumption	<i>Q<sub>HE</sub></i>	3,447	kWh or GJ					
For heat pump combination heater:								
Declared load profile	L				Water heating energy efficiency	$\eta_{wh}$	117	%
Daily electricity consumption	<i>Q<sub>elec</sub></i>	4.140	kWh		Daily fuel consumption	<i>Q<sub>fuel</sub></i>	0.000	kWh
Annual electricity consumption	<i>AEC</i>	877	kWh		Annual fuel consumption	<i>AFC</i>	0	GJ
Daikin Europe N.V. - Zandvoordestraat 300, 8400 Oostende, Belgium		Daikin Europe N.V.						

<sup>(3)</sup> ) For heat pump space heaters and heat pump combination heaters, the rated heat output 'Prated' is equal to the design load for heating 'Pdesignh', and the rated heat output of a supplementary heater 'Psup' is equal to the supplementary capacity for heating 'sup(Tj)'.  
<sup>(4)</sup> If 'Cdh' is not determined by measurement then the default degradation coefficient is 'Cdh' = 0.9.